



WOLTIO

Single-phase EV charger

SELECT & PRO

Designed and manufactured in Europe

Our Accesories


SmartEnable Key

Automatically authorises the recharge of your electric car by proximity.
Configure up to four different keys per charger.



Photovoltaic Kit

Ideal solution for integrating with photovoltaic installations. Save on your EV charging costs.




Cable Holder

Perfect solution for keeping the charging cable organized.



Extra socket kit

An extra socket at your charging point, allowing you to connect electrical devices up to 230V.
(Accessory compatible with the WOLTIO PRO)



You can find us at



www.woltio.com



Download our App



Last generation EV charger

Designed to provide a safe, optimized, and hassle-free charging experience. Compatible with **ALL** electric and plug-in hybrid vehicles.



EV charger installations made easy

Save time and money during installation thanks to integrated protections (PRO model).



Indoor and outdoor usage

A versatile solution for your home, designed for installations in both indoor and outdoor settings.



Charging optimization

Dynamic power control ensures maximum charging speed without exceeding your contract.



Bluetooth connectivity and App

Monitor your home's consumption and the energy generated by your photovoltaic installation, configure your charger, download monthly reports. Updates even in areas without network.



Power Management

Manage the power of two chargers in a single installation.

WOLTIO SELECT & PRO

General specifications

Connector: Type 2 (7.4kW)

Dimensions (without cable): 298 x 248 x 170 mm

Cable length: 5 or 7 m

Electrical specifications

Maximum charging power: 7.4 kW

AC voltage range \pm 10%: from 220V to 240V (7.4kW)

Maximum current: 32 A

Configurable charging current: from 6A to max current

Protection degree: IP54 / IK08

Dynamic power control: current probe included

User interface and communications

Connectivity: Bluetooth 4.1

Equipment configuration: WOLTIO mobile app

Charger status information: 2.8" display

Wired connectivity: RS485 Modbus RTU



WOLTIO PRO

Integrated protections

Differential, circuit breaker, and protection against permanent and transient overvoltages.

Automatic reconnection integrated within the charger.