

Our Accesories

SmartEnable Key

Automatically authorises the recharge of your electric car by proximity.

Configure up to four different keys per charger.



Cable Holder

Perfect solution for keeping the charging cable organized.



OCPP Communications Module

Enables remote user management and billing.



You can find us at











Download our App







WOLTIO PLUS

General specifications

Connector: Type 2 Dimensions (without cable): 298 x 248 x 170 mm Cable length: 5 or 7 m

Electrical specifications

Maximum charging power: 22 kW

AC voltage range +- 10%: 400V (22kW)

Maximum current: 32 A

Configurable charging current: from 6A to max current

Protection degree: IP54 / IK08

User interface and communications

Connectivity: Bluetooth 4.1 Equipment configuration: WOLTIO mobile app Charger status information: 2.8" display Wired connectivity: RS485 Modbus RTU Ethernet/WiFi connectivity: Optional OCPP 1.6 module

Last generation EV charger

Designed to provide a safe, optimized, and hassle-free charging experience. Compatible with **ALL** electric and plug-in hybrid vehicles.



Indoor and outdoor usage

A versatile solution for your home, designed for installations in both indoor and outdoor settings.



Bluetooth connectivity and App

Monitor your home's consumption and the energy generated by your photovoltaic installation, configure your charger, download monthly reports. Updates even in areas without network.



Power Management

Manage the power of two chargers in a single installation.

